


GOLD LABEL Banded Narrow - Product Description



V-Belt Banded

GOLD LABEL.



Metric			
Section	W - Width (mm)	H - Height (mm)	Weight (Kg/rib*m)
3V	9	10	0.099
5V	15	15.5	0.272
8V	25	25.5	0.654

Imperial			
Section	W - Width (in)	H - Height (in)	Weight (lb/rib*in)
3V	23/64	25/64	0.006
5V	19/32	39/64	0.015
8V	1	1	0.037

V-Belt Banded

Part Number Description: **5/8V1050GL**

5/: Numer of Ribs

8V: Profile

1050: Internal Length (mm)

GL: Gold Label

Features and Benefits:

Tie Band Fabric: PET/Cotton, CR Impregnated

- Abrasion, wear and Oil Resistance
- Prevents Vibrations and belt Turn-over

Fabric Cover: PET/Cotton, CR Impregnated

- Abrasion, wear and Oil Resistance
- Static Conductivity: ISO 1813

Tension Cords: High Modulus Polyester

- Superior Dimensional stability (low stretch and tension decay)
- High resistance to overloads and shock loads

Compression Rubber: SBR/NR Rubber blend

- Resistant to bending stress
- Superior Oil and Heat resistance
- Temperature Range: -35 To +70 C. / -31 To 160 F.

Wedge Profile (RMA): Up to 3 times the Power transmission capacity compared to Classical V Profiles (A, B, C, D, E)
Designed for OEMs

Markets and Applications:

Ideal solution for shock or pulsating loads

Designed for heavy duty drives

Recommended solution for multiple belts drives where single belts vibrate or turn over

Pulley Standards: RMA IP22

GOLD LABEL Banded Narrow - Size List



V-Belt Banded

GOLD LABEL.



Metric			
Section	W - Width (mm)	H - Height (mm)	Weight (Kg/rib*m)
3V	9	10	0.099
5V	15	15.5	0.272
8V	25	25.5	0.654

Imperial			
Section	W - Width (in)	H - Height (in)	Weight (lb/rib*in)
3V	23/64	25/64	0.006
5V	19/32	39/64	0.015
8V	1	1	0.037

DAYCO Part Nr	Section	Lo Outside length (mm)	Lo Outside length (in)	Weight (Kg)	Weight (lbs)
2/3V520GL	3V	1321	52.00	0.26	0.58
3/3V520GL	3V	1321	52.00	0.39	0.87
4/3V520GL	3V	1321	52.00	0.52	1.15
5/3V520GL	3V	1321	52.00	0.66	1.44
24/3V520GL	3V	1321	52.00	3.15	6.93
2/3V530GL	3V	1346	53.00	0.27	0.59
3/3V530GL	3V	1346	53.00	0.40	0.88
4/3V530GL	3V	1346	53.00	0.53	1.18
5/3V530GL	3V	1346	53.00	0.67	1.47
24/3V530GL	3V	1346	53.00	3.20	7.06
2/3V560GL	3V	1422	56.00	0.28	0.62
3/3V560GL	3V	1422	56.00	0.42	0.93
4/3V560GL	3V	1422	56.00	0.56	1.24
5/3V560GL	3V	1422	56.00	0.71	1.55
24/3V560GL	3V	1422	56.00	3.39	7.46
2/3V600GL	3V	1524	60.00	0.30	0.67
3/3V600GL	3V	1524	60.00	0.45	1.00
4/3V600GL	3V	1524	60.00	0.60	1.33
5/3V600GL	3V	1524	60.00	0.76	1.67
24/3V600GL	3V	1524	60.00	3.63	7.99
2/3V630GL	3V	1600	63.00	0.32	0.70
3/3V630GL	3V	1600	63.00	0.48	1.05
4/3V630GL	3V	1600	63.00	0.63	1.40
5/3V630GL	3V	1600	63.00	0.79	1.75
24/3V630GL	3V	1600	63.00	3.81	8.39
2/3V670GL	3V	1702	67.00	0.34	0.74
3/3V670GL	3V	1702	67.00	0.51	1.12
4/3V670GL	3V	1702	67.00	0.68	1.49
5/3V670GL	3V	1702	67.00	0.84	1.86
24/3V670GL	3V	1702	67.00	4.05	8.93
2/3V710GL	3V	1803	71.00	0.36	0.79
3/3V710GL	3V	1803	71.00	0.54	1.18
4/3V710GL	3V	1803	71.00	0.72	1.58
5/3V710GL	3V	1803	71.00	0.89	1.97
24/3V710GL	3V	1803	71.00	4.29	9.46
2/3V750GL	3V	1905	75.00	0.38	0.83
3/3V750GL	3V	1905	75.00	0.57	1.25
4/3V750GL	3V	1905	75.00	0.76	1.67
5/3V750GL	3V	1905	75.00	0.95	2.08
24/3V750GL	3V	1905	75.00	4.54	9.99

GOLD LABEL Banded Narrow - Size List



V-Belt Banded

GOLD LABEL.



Metric			
Section	W - Width (mm)	H - Height (mm)	Weight (Kg/rib*m)
3V	9	10	0.099
5V	15	15.5	0.272
8V	25	25.5	0.654

Imperial			
Section	W - Width (in)	H - Height (in)	Weight (lb/rib*in)
3V	23/64	25/64	0.006
5V	19/32	39/64	0.015
8V	1	1	0.037

DAYCO Part Nr	Section	Lo Outside length (mm)	Lo Outside length (in)	Weight (Kg)	Weight (lbs)
2/3V800GL	3V	2032	80.00	0.40	0.89
3/3V800GL	3V	2032	80.00	0.60	1.33
4/3V800GL	3V	2032	80.00	0.81	1.78
5/3V800GL	3V	2032	80.00	1.01	2.22
24/3V800GL	3V	2032	80.00	4.84	10.66
2/3V830GL	3V	2108	83.00	0.42	0.92
3/3V830GL	3V	2108	83.00	0.63	1.38
4/3V830GL	3V	2108	83.00	0.84	1.84
5/3V830GL	3V	2108	83.00	1.05	2.30
24/3V830GL	3V	2108	83.00	5.02	11.06
2/3V850GL	3V	2159	85.00	0.43	0.94
3/3V850GL	3V	2159	85.00	0.64	1.42
4/3V850GL	3V	2159	85.00	0.86	1.89
5/3V850GL	3V	2159	85.00	1.07	2.36
24/3V850GL	3V	2159	85.00	5.14	11.32
2/3V900GL	3V	2286	90.00	0.45	1.00
3/3V900GL	3V	2286	90.00	0.68	1.50
4/3V900GL	3V	2286	90.00	0.91	2.00
5/3V900GL	3V	2286	90.00	1.13	2.50
24/3V900GL	3V	2286	90.00	5.44	11.99
2/3V950GL	3V	2413	95.00	0.48	1.05
3/3V950GL	3V	2413	95.00	0.72	1.58
4/3V950GL	3V	2413	95.00	0.96	2.11
5/3V950GL	3V	2413	95.00	1.20	2.64
24/3V950GL	3V	2413	95.00	5.75	12.66
2/3V1000GL	3V	2540	100.00	0.50	1.11
3/3V1000GL	3V	2540	100.00	0.76	1.67
4/3V1000GL	3V	2540	100.00	1.01	2.22
5/3V1000GL	3V	2540	100.00	1.26	2.78
24/3V1000GL	3V	2540	100.00	6.05	13.32
2/3V1060GL	3V	2692	106.00	0.53	1.18
3/3V1060GL	3V	2692	106.00	0.80	1.76
4/3V1060GL	3V	2692	106.00	1.07	2.35
5/3V1060GL	3V	2692	106.00	1.34	2.94
24/3V1060GL	3V	2692	106.00	6.41	14.12
2/3V1120GL	3V	2845	112.00	0.56	1.24
3/3V1120GL	3V	2845	112.00	0.85	1.87
4/3V1120GL	3V	2845	112.00	1.13	2.49
5/3V1120GL	3V	2845	112.00	1.41	3.11
24/3V1120GL	3V	2845	112.00	6.77	14.92

GOLD LABEL Banded Narrow - Size List



V-Belt Banded

GOLD LABEL.



Metric			
Section	W - Width (mm)	H - Height (mm)	Weight (Kg/rib*m)
3V	9	10	0.099
5V	15	15.5	0.272
8V	25	25.5	0.654

Imperial			
Section	W - Width (in)	H - Height (in)	Weight (lb/rib*in)
3V	23/64	25/64	0.006
5V	19/32	39/64	0.015
8V	1	1	0.037


DAYCO Part Nr	Section	Lo Outside length (mm)	Lo Outside length (in)	Weight (Kg)	Weight (lbs)
2/3V1180GL	3V	2997	118.00	0.59	1.31
3/3V1180GL	3V	2997	118.00	0.89	1.96
4/3V1180GL	3V	2997	118.00	1.19	2.62
5/3V1180GL	3V	2997	118.00	1.49	3.27
24/3V1180GL	3V	2997	118.00	7.14	15.72
2/3V1250GL	3V	3175	125.00	0.63	1.39
3/3V1250GL	3V	3175	125.00	0.95	2.08
4/3V1250GL	3V	3175	125.00	1.26	2.78
5/3V1250GL	3V	3175	125.00	1.58	3.47
24/3V1250GL	3V	3175	125.00	7.56	16.65
2/3V1320GL	3V	3353	132.00	0.67	1.47
3/3V1320GL	3V	3353	132.00	1.00	2.20
4/3V1320GL	3V	3353	132.00	1.33	2.93
5/3V1320GL	3V	3353	132.00	1.66	3.66
24/3V1320GL	3V	3353	132.00	7.98	17.59
2/3V1400GL	3V	3556	140.00	0.71	1.55
3/3V1400GL	3V	3556	140.00	1.06	2.33
4/3V1400GL	3V	3556	140.00	1.41	3.11
5/3V1400GL	3V	3556	140.00	1.76	3.89
24/3V1400GL	3V	3556	140.00	8.47	18.65
2/5V510GL	5V	1295	51.00	0.70	1.55
3/5V510GL	5V	1295	51.00	1.06	2.32
4/5V510GL	5V	1295	51.00	1.41	3.10
5/5V510GL	5V	1295	51.00	1.76	3.87
16/5V510GL	5V	1295	51.00	5.63	12.40
2/5V530GL	5V	1346	53.00	0.73	1.61
3/5V530GL	5V	1346	53.00	1.10	2.42
4/5V530GL	5V	1346	53.00	1.46	3.22
5/5V530GL	5V	1346	53.00	1.83	4.03
16/5V530GL	5V	1346	53.00	5.85	12.89
2/5V560GL	5V	1422	56.00	0.77	1.70
3/5V560GL	5V	1422	56.00	1.16	2.55
4/5V560GL	5V	1422	56.00	1.55	3.40
5/5V560GL	5V	1422	56.00	1.93	4.25
16/5V560GL	5V	1422	56.00	6.18	13.61
2/5V600GL	5V	1524	60.00	0.83	1.82
3/5V600GL	5V	1524	60.00	1.24	2.74
4/5V600GL	5V	1524	60.00	1.66	3.65
5/5V600GL	5V	1524	60.00	2.07	4.56
16/5V600GL	5V	1524	60.00	6.62	14.59

GOLD LABEL Banded Narrow - Size List



V-Belt Banded

GOLD LABEL.



Metric			
Section	W - Width (mm)	H - Height (mm)	Weight (Kg/rib*m)
3V	9	10	0.099
5V	15	15.5	0.272
8V	25	25.5	0.654

Imperial			
Section	W - Width (in)	H - Height (in)	Weight (lb/rib*in)
3V	23/64	25/64	0.006
5V	19/32	39/64	0.015
8V	1	1	0.037

DAYCO Part Nr	Section	Lo Outside length (mm)	Lo Outside length (in)	Weight (Kg)	Weight (lbs)
2/5V630GL	5V	1600	63.00	0.87	1.91
3/5V630GL	5V	1600	63.00	1.30	2.87
4/5V630GL	5V	1600	63.00	1.74	3.83
5/5V630GL	5V	1600	63.00	2.17	4.79
16/5V630GL	5V	1600	63.00	6.95	15.32
2/5V670GL	5V	1702	67.00	0.92	2.04
3/5V670GL	5V	1702	67.00	1.39	3.06
4/5V670GL	5V	1702	67.00	1.85	4.07
5/5V670GL	5V	1702	67.00	2.31	5.09
16/5V670GL	5V	1702	67.00	7.40	16.29
2/5V710GL	5V	1803	71.00	0.98	2.16
3/5V710GL	5V	1803	71.00	1.47	3.24
4/5V710GL	5V	1803	71.00	1.96	4.32
5/5V710GL	5V	1803	71.00	2.45	5.39
16/5V710GL	5V	1803	71.00	7.84	17.26
2/5V750GL	5V	1905	75.00	1.04	2.28
3/5V750GL	5V	1905	75.00	1.55	3.42
4/5V750GL	5V	1905	75.00	2.07	4.56
5/5V750GL	5V	1905	75.00	2.59	5.70
16/5V750GL	5V	1905	75.00	8.28	18.24
2/5V800GL	5V	2032	80.00	1.10	2.43
3/5V800GL	5V	2032	80.00	1.66	3.65
4/5V800GL	5V	2032	80.00	2.21	4.86
5/5V800GL	5V	2032	80.00	2.76	6.08
16/5V800GL	5V	2032	80.00	8.83	19.45
2/5V850GL	5V	2159	85.00	1.17	2.58
3/5V850GL	5V	2159	85.00	1.76	3.88
4/5V850GL	5V	2159	85.00	2.35	5.17
5/5V850GL	5V	2159	85.00	2.93	6.46
16/5V850GL	5V	2159	85.00	9.38	20.67
2/5V900GL	5V	2286	90.00	1.24	2.74
3/5V900GL	5V	2286	90.00	1.86	4.10
4/5V900GL	5V	2286	90.00	2.48	5.47
5/5V900GL	5V	2286	90.00	3.11	6.84
16/5V900GL	5V	2286	90.00	9.94	21.89
2/5V950GL	5V	2413	95.00	1.31	2.89
3/5V950GL	5V	2413	95.00	1.97	4.33
4/5V950GL	5V	2413	95.00	2.62	5.78
5/5V950GL	5V	2413	95.00	3.28	7.22
16/5V950GL	5V	2413	95.00	10.49	23.10

GOLD LABEL Banded Narrow - Size List



V-Belt Banded

GOLD LABEL.



Metric			
Section	W - Width (mm)	H - Height (mm)	Weight (Kg/rib*m)
3V	9	10	0.099
5V	15	15.5	0.272
8V	25	25.5	0.654

Imperial			
Section	W - Width (in)	H - Height (in)	Weight (lb/rib*in)
3V	23/64	25/64	0.006
5V	19/32	39/64	0.015
8V	1	1	0.037


DAYCO Part Nr	Section	Lo Outside length (mm)	Lo Outside length (in)	Weight (Kg)	Weight (lbs)
2/5V975GL	5V	2477	97.50	1.35	2.96
3/5V975GL	5V	2477	97.50	2.02	4.45
4/5V975GL	5V	2477	97.50	2.69	5.93
5/5V975GL	5V	2477	97.50	3.36	7.41
16/5V975GL	5V	2477	97.50	10.77	23.71
2/5V1000GL	5V	2540	100.00	1.38	3.04
3/5V1000GL	5V	2540	100.00	2.07	4.56
4/5V1000GL	5V	2540	100.00	2.76	6.08
5/5V1000GL	5V	2540	100.00	3.45	7.60
16/5V1000GL	5V	2540	100.00	11.04	24.32
2/5V1060GL	5V	2692	106.00	1.46	3.22
3/5V1060GL	5V	2692	106.00	2.19	4.83
4/5V1060GL	5V	2692	106.00	2.93	6.44
5/5V1060GL	5V	2692	106.00	3.66	8.05
16/5V1060GL	5V	2692	106.00	11.70	25.77
2/5V1120GL	5V	2845	112.00	1.55	3.40
3/5V1120GL	5V	2845	112.00	2.32	5.11
4/5V1120GL	5V	2845	112.00	3.09	6.81
5/5V1120GL	5V	2845	112.00	3.86	8.51
16/5V1120GL	5V	2845	112.00	12.37	27.24
2/5V1180GL	5V	2997	118.00	1.63	3.59
3/5V1180GL	5V	2997	118.00	2.44	5.38
4/5V1180GL	5V	2997	118.00	3.26	7.17
5/5V1180GL	5V	2997	118.00	4.07	8.97
16/5V1180GL	5V	2997	118.00	13.03	28.69
2/5V1200GL	5V	3048	120.00	1.66	3.65
3/5V1200GL	5V	3048	120.00	2.48	5.47
4/5V1200GL	5V	3048	120.00	3.31	7.30
5/5V1200GL	5V	3048	120.00	4.14	9.12
16/5V1200GL	5V	3048	120.00	13.25	29.18
2/5V1210GL	5V	3073	121.00	1.67	3.68
3/5V1210GL	5V	3073	121.00	2.50	5.52
4/5V1210GL	5V	3073	121.00	3.34	7.35
5/5V1210GL	5V	3073	121.00	4.17	9.19
16/5V1210GL	5V	3073	121.00	13.36	29.42
2/5V1250GL	5V	3175	125.00	1.73	3.80
3/5V1250GL	5V	3175	125.00	2.59	5.70
4/5V1250GL	5V	3175	125.00	3.45	7.60
5/5V1250GL	5V	3175	125.00	4.31	9.50
16/5V1250GL	5V	3175	125.00	13.80	30.40

GOLD LABEL Banded Narrow - Size List



V-Belt Banded

GOLD LABEL.



Metric			
Section	W - Width (mm)	H - Height (mm)	Weight (Kg/rib*m)
3V	9	10	0.099
5V	15	15.5	0.272
8V	25	25.5	0.654

Imperial			
Section	W - Width (in)	H - Height (in)	Weight (lb/rib*in)
3V	23/64	25/64	0.006
5V	19/32	39/64	0.015
8V	1	1	0.037

DAYCO Part Nr	Section	Lo Outside length (mm)	Lo Outside length (in)	Weight (Kg)	Weight (lbs)
2/5V1320GL	5V	3353	132.00	1.82	4.01
3/5V1320GL	5V	3353	132.00	2.73	6.02
4/5V1320GL	5V	3353	132.00	3.64	8.03
5/5V1320GL	5V	3353	132.00	4.55	10.03
16/5V1320GL	5V	3353	132.00	14.57	32.10
2/5V1400GL	5V	3556	140.00	1.93	4.26
3/5V1400GL	5V	3556	140.00	2.90	6.38
4/5V1400GL	5V	3556	140.00	3.86	8.51
5/5V1400GL	5V	3556	140.00	4.83	10.64
16/5V1400GL	5V	3556	140.00	15.46	34.04
2/5V1500GL	5V	3810	150.00	2.07	4.56
3/5V1500GL	5V	3810	150.00	3.11	6.84
4/5V1500GL	5V	3810	150.00	4.14	9.12
5/5V1500GL	5V	3810	150.00	5.18	11.40
16/5V1500GL	5V	3810	150.00	16.56	36.48
2/5V1600GL	5V	4064	160.00	2.21	4.86
3/5V1600GL	5V	4064	160.00	3.31	7.30
4/5V1600GL	5V	4064	160.00	4.42	9.73
5/5V1600GL	5V	4064	160.00	5.52	12.16
16/5V1600GL	5V	4064	160.00	17.66	38.91
2/5V1650GL	5V	4191	165.00	2.28	5.02
3/5V1650GL	5V	4191	165.00	3.42	7.52
4/5V1650GL	5V	4191	165.00	4.55	10.03
5/5V1650GL	5V	4191	165.00	5.69	12.54
16/5V1650GL	5V	4191	165.00	18.22	40.12
2/5V1700GL	5V	4318	170.00	2.35	5.17
3/5V1700GL	5V	4318	170.00	3.52	7.75
4/5V1700GL	5V	4318	170.00	4.69	10.33
5/5V1700GL	5V	4318	170.00	5.87	12.92
16/5V1700GL	5V	4318	170.00	18.77	41.34
2/5V1800GL	5V	4572	180.00	2.48	5.47
3/5V1800GL	5V	4572	180.00	3.73	8.21
4/5V1800GL	5V	4572	180.00	4.97	10.94
5/5V1800GL	5V	4572	180.00	6.21	13.68
16/5V1800GL	5V	4572	180.00	19.87	43.77
2/5V1900GL	5V	4826	190.00	2.62	5.78
3/5V1900GL	5V	4826	190.00	3.93	8.66
4/5V1900GL	5V	4826	190.00	5.24	11.55
5/5V1900GL	5V	4826	190.00	6.56	14.44
16/5V1900GL	5V	4826	190.00	20.98	46.20

GOLD LABEL Banded Narrow - Size List



V-Belt Banded

GOLD LABEL.



Metric			
Section	W - Width (mm)	H - Height (mm)	Weight (Kg/rib*m)
3V	9	10	0.099
5V	15	15.5	0.272
8V	25	25.5	0.654

Imperial			
Section	W - Width (in)	H - Height (in)	Weight (lb/rib*in)
3V	23/64	25/64	0.006
5V	19/32	39/64	0.015
8V	1	1	0.037

DAYCO Part Nr	Section	Lo Outside length (mm)	Lo Outside length (in)	Weight (Kg)	Weight (lbs)
2/5V2000GL	5V	5080	200.00	2.76	6.08
3/5V2000GL	5V	5080	200.00	4.14	9.12
4/5V2000GL	5V	5080	200.00	5.52	12.16
5/5V2000GL	5V	5080	200.00	6.90	15.20
16/5V2000GL	5V	5080	200.00	22.08	48.63
2/5V2120GL	5V	5385	212.00	2.93	6.44
3/5V2120GL	5V	5385	212.00	4.39	9.67
4/5V2120GL	5V	5385	212.00	5.85	12.89
5/5V2120GL	5V	5385	212.00	7.31	16.11
16/5V2120GL	5V	5385	212.00	23.41	51.55
2/5V2240GL	5V	5690	224.00	3.09	6.81
3/5V2240GL	5V	5690	224.00	4.64	10.21
4/5V2240GL	5V	5690	224.00	6.18	13.62
5/5V2240GL	5V	5690	224.00	7.73	17.02
16/5V2240GL	5V	5690	224.00	24.73	54.47
2/5V2350GL	5V	5969	235.00	3.24	7.14
3/5V2350GL	5V	5969	235.00	4.86	10.71
4/5V2350GL	5V	5969	235.00	6.49	14.29
5/5V2350GL	5V	5969	235.00	8.11	17.86
16/5V2350GL	5V	5969	235.00	25.94	57.15
2/5V2360GL	5V	5994	236.00	3.26	7.17
3/5V2360GL	5V	5994	236.00	4.88	10.76
4/5V2360GL	5V	5994	236.00	6.51	14.35
5/5V2360GL	5V	5994	236.00	8.14	17.93
16/5V2360GL	5V	5994	236.00	26.05	57.38
2/5V2500GL	5V	6350	250.00	3.45	7.60
3/5V2500GL	5V	6350	250.00	5.18	11.40
4/5V2500GL	5V	6350	250.00	6.90	15.20
5/5V2500GL	5V	6350	250.00	8.63	19.00
16/5V2500GL	5V	6350	250.00	27.60	60.79
2/5V2600GL	5V	6604	260.00	3.59	7.90
3/5V2600GL	5V	6604	260.00	5.38	11.85
4/5V2600GL	5V	6604	260.00	7.18	15.81
5/5V2600GL	5V	6604	260.00	8.97	19.76
16/5V2600GL	5V	6604	260.00	28.70	63.22
2/5V2650GL	5V	6731	265.00	3.66	8.06
3/5V2650GL	5V	6731	265.00	5.49	12.08
4/5V2650GL	5V	6731	265.00	7.31	16.11
5/5V2650GL	5V	6731	265.00	9.14	20.14
16/5V2650GL	5V	6731	265.00	29.26	64.44

GOLD LABEL Banded Narrow - Size List



V-Belt Banded

GOLD LABEL.



Metric			
Section	W - Width (mm)	H - Height (mm)	Weight (Kg/rib*m)
3V	9	10	0.099
5V	15	15.5	0.272
8V	25	25.5	0.654

Imperial			
Section	W - Width (in)	H - Height (in)	Weight (lb/rib*in)
3V	23/64	25/64	0.006
5V	19/32	39/64	0.015
8V	1	1	0.037


DAYCO Part Nr	Section	Lo Outside length (mm)	Lo Outside length (in)	Weight (Kg)	Weight (lbs)
2/5V2800GL	5V	7112	280.00	3.86	8.51
3/5V2800GL	5V	7112	280.00	5.80	12.77
4/5V2800GL	5V	7112	280.00	7.73	17.02
5/5V2800GL	5V	7112	280.00	9.66	21.28
16/5V2800GL	5V	7112	280.00	30.91	68.09
2/5V3000GL	5V	7620	300.00	4.14	9.12
3/5V3000GL	5V	7620	300.00	6.21	13.68
4/5V3000GL	5V	7620	300.00	8.28	18.24
5/5V3000GL	5V	7620	300.00	10.35	22.80
16/5V3000GL	5V	7620	300.00	33.12	72.95
2/5V3150GL	5V	8001	315.00	4.35	9.57
3/5V3150GL	5V	8001	315.00	6.52	14.36
4/5V3150GL	5V	8001	315.00	8.69	19.15
5/5V3150GL	5V	8001	315.00	10.87	23.94
16/5V3150GL	5V	8001	315.00	34.78	76.60
2/5V3350GL	5V	8509	335.00	4.62	10.18
3/5V3350GL	5V	8509	335.00	6.93	15.27
4/5V3350GL	5V	8509	335.00	9.25	20.37
5/5V3350GL	5V	8509	335.00	11.56	25.46
16/5V3350GL	5V	8509	335.00	36.98	81.46
2/5V3550GL	5V	9017	355.00	4.90	10.79
3/5V3550GL	5V	9017	355.00	7.35	16.19
4/5V3550GL	5V	9017	355.00	9.80	21.58
5/5V3550GL	5V	9017	355.00	12.25	26.98
16/5V3550GL	5V	9017	355.00	39.19	86.33
2/8V1180GL	8V	2997	118.00	3.92	8.63
3/8V1180GL	8V	2997	118.00	5.88	12.94
4/8V1180GL	8V	2997	118.00	7.83	17.26
5/8V1180GL	8V	2997	118.00	9.79	21.57
12/8V1180GL	8V	2997	118.00	23.50	51.77
2/8V1250GL	8V	3175	125.00	4.15	9.14
3/8V1250GL	8V	3175	125.00	6.23	13.71
4/8V1250GL	8V	3175	125.00	8.30	18.28
5/8V1250GL	8V	3175	125.00	10.38	22.85
12/8V1250GL	8V	3175	125.00	24.90	54.85
2/8V1320GL	8V	3353	132.00	4.38	9.65
3/8V1320GL	8V	3353	132.00	6.57	14.48
4/8V1320GL	8V	3353	132.00	8.77	19.31
5/8V1320GL	8V	3353	132.00	10.96	24.13
12/8V1320GL	8V	3353	132.00	26.30	57.92

GOLD LABEL Banded Narrow - Size List



V-Belt Banded

GOLD LABEL.




Metric			
Section	W - Width (mm)	H - Height (mm)	Weight (Kg/rib*m)
3V	9	10	0.099
5V	15	15.5	0.272
8V	25	25.5	0.654

Imperial			
Section	W - Width (in)	H - Height (in)	Weight (lb/rib*in)
3V	23/64	25/64	0.006
5V	19/32	39/64	0.015
8V	1	1	0.037


DAYCO Part Nr	Section	Lo Outside length (mm)	Lo Outside length (in)	Weight (Kg)	Weight (lbs)
2/8V1400GL	8V	3556	140.00	4.65	10.24
3/8V1400GL	8V	3556	140.00	6.97	15.36
4/8V1400GL	8V	3556	140.00	9.30	20.48
5/8V1400GL	8V	3556	140.00	11.62	25.59
12/8V1400GL	8V	3556	140.00	27.89	61.43
2/8V1500GL	8V	3810	150.00	4.98	10.97
3/8V1500GL	8V	3810	150.00	7.47	16.45
4/8V1500GL	8V	3810	150.00	9.96	21.94
5/8V1500GL	8V	3810	150.00	12.45	27.42
12/8V1500GL	8V	3810	150.00	29.88	65.81
2/8V1600GL	8V	4064	160.00	5.31	11.70
3/8V1600GL	8V	4064	160.00	7.97	17.55
4/8V1600GL	8V	4064	160.00	10.62	23.40
5/8V1600GL	8V	4064	160.00	13.28	29.25
12/8V1600GL	8V	4064	160.00	31.87	70.20
2/8V1650GL	8V	4191	165.00	5.48	12.07
3/8V1650GL	8V	4191	165.00	8.22	18.10
4/8V1650GL	8V	4191	165.00	10.96	24.13
5/8V1650GL	8V	4191	165.00	13.70	30.17
12/8V1650GL	8V	4191	165.00	32.87	72.40
2/8V1700GL	8V	4318	170.00	5.64	12.43
3/8V1700GL	8V	4318	170.00	8.47	18.65
4/8V1700GL	8V	4318	170.00	11.29	24.86
5/8V1700GL	8V	4318	170.00	14.11	31.08
12/8V1700GL	8V	4318	170.00	33.86	74.59
2/8V1800GL	8V	4572	180.00	5.98	13.16
3/8V1800GL	8V	4572	180.00	8.96	19.74
4/8V1800GL	8V	4572	180.00	11.95	26.33
5/8V1800GL	8V	4572	180.00	14.94	32.91
12/8V1800GL	8V	4572	180.00	35.86	78.98
2/8V1900GL	8V	4826	190.00	6.31	13.89
3/8V1900GL	8V	4826	190.00	9.46	20.84
4/8V1900GL	8V	4826	190.00	12.62	27.79
5/8V1900GL	8V	4826	190.00	15.77	34.74
12/8V1900GL	8V	4826	190.00	37.85	83.37
2/8V2000GL	8V	5080	200.00	6.64	14.63
3/8V2000GL	8V	5080	200.00	9.96	21.94
4/8V2000GL	8V	5080	200.00	13.28	29.25
5/8V2000GL	8V	5080	200.00	16.60	36.56
12/8V2000GL	8V	5080	200.00	39.84	87.75

GOLD LABEL Banded Narrow - Size List



V-Belt Banded

GOLD LABEL.



Metric			
Section	W - Width (mm)	H - Height (mm)	Weight (Kg/rib*m)
3V	9	10	0.099
5V	15	15.5	0.272
8V	25	25.5	0.654

Imperial			
Section	W - Width (in)	H - Height (in)	Weight (lb/rib*in)
3V	23/64	25/64	0.006
5V	19/32	39/64	0.015
8V	1	1	0.037


DAYCO Part Nr	Section	Lo Outside length (mm)	Lo Outside length (in)	Weight (Kg)	Weight (lbs)
2/8V2120GL	8V	5385	212.00	7.04	15.50
3/8V2120GL	8V	5385	212.00	10.56	23.26
4/8V2120GL	8V	5385	212.00	14.08	31.01
5/8V2120GL	8V	5385	212.00	17.60	38.76
12/8V2120GL	8V	5385	212.00	42.23	93.02
2/8V2240GL	8V	5690	224.00	7.44	16.38
3/8V2240GL	8V	5690	224.00	11.16	24.57
4/8V2240GL	8V	5690	224.00	14.87	32.76
5/8V2240GL	8V	5690	224.00	18.59	40.95
12/8V2240GL	8V	5690	224.00	44.62	98.29
2/8V2360GL	8V	5994	236.00	7.83	17.26
3/8V2360GL	8V	5994	236.00	11.75	25.89
4/8V2360GL	8V	5994	236.00	15.67	34.51
5/8V2360GL	8V	5994	236.00	19.59	43.14
12/8V2360GL	8V	5994	236.00	47.01	103.54
2/8V2400GL	8V	6096	240.00	7.97	17.55
3/8V2400GL	8V	6096	240.00	11.95	26.33
4/8V2400GL	8V	6096	240.00	15.94	35.10
5/8V2400GL	8V	6096	240.00	19.92	43.88
12/8V2400GL	8V	6096	240.00	47.81	105.30
2/8V2500GL	8V	6350	250.00	8.30	18.28
3/8V2500GL	8V	6350	250.00	12.45	27.42
4/8V2500GL	8V	6350	250.00	16.60	36.56
5/8V2500GL	8V	6350	250.00	20.75	45.70
12/8V2500GL	8V	6350	250.00	49.80	109.69
2/8V2650GL	8V	6731	265.00	8.80	19.38
3/8V2650GL	8V	6731	265.00	13.20	29.07
4/8V2650GL	8V	6731	265.00	17.60	38.76
5/8V2650GL	8V	6731	265.00	22.00	48.45
12/8V2650GL	8V	6731	265.00	52.79	116.27
2/8V2800GL	8V	7112	280.00	9.30	20.48
3/8V2800GL	8V	7112	280.00	13.94	30.71
4/8V2800GL	8V	7112	280.00	18.59	40.95
5/8V2800GL	8V	7112	280.00	23.24	51.19
12/8V2800GL	8V	7112	280.00	55.78	122.85
2/8V3000GL	8V	7620	300.00	9.96	21.94
3/8V3000GL	8V	7620	300.00	14.94	32.91
4/8V3000GL	8V	7620	300.00	19.92	43.88
5/8V3000GL	8V	7620	300.00	24.90	54.85
12/8V3000GL	8V	7620	300.00	59.76	131.63

GOLD LABEL Banded Narrow - Size List



V-Belt Banded

GOLD LABEL.



Metric			
Section	W - Width (mm)	H - Height (mm)	Weight (Kg/rib*m)
3V	9	10	0.099
5V	15	15.5	0.272
8V	25	25.5	0.654

Imperial			
Section	W - Width (in)	H - Height (in)	Weight (lb/rib*in)
3V	23/64	25/64	0.006
5V	19/32	39/64	0.015
8V	1	1	0.037

DAYCO Part Nr	Section	Lo Outside length (mm)	Lo Outside length (in)	Weight (Kg)	Weight (lbs)
2/8V3150GL	8V	8001	315.00	10.46	23.04
3/8V3150GL	8V	8001	315.00	15.69	34.55
4/8V3150GL	8V	8001	315.00	20.92	46.07
5/8V3150GL	8V	8001	315.00	26.15	57.59
12/8V3150GL	8V	8001	315.00	62.75	138.21
2/8V3350GL	8V	8509	335.00	11.12	24.50
3/8V3350GL	8V	8509	335.00	16.68	36.75
4/8V3350GL	8V	8509	335.00	22.24	49.00
5/8V3350GL	8V	8509	335.00	27.81	61.24
12/8V3350GL	8V	8509	335.00	66.73	146.99
2/8V3550GL	8V	9017	355.00	11.79	25.96
3/8V3550GL	8V	9017	355.00	17.68	38.94
4/8V3550GL	8V	9017	355.00	23.57	51.92
5/8V3550GL	8V	9017	355.00	29.47	64.90
12/8V3550GL	8V	9017	355.00	70.72	155.76
2/8V3750GL	8V	9525	375.00	12.45	27.42
3/8V3750GL	8V	9525	375.00	18.68	41.13
4/8V3750GL	8V	9525	375.00	24.90	54.85
5/8V3750GL	8V	9525	375.00	31.13	68.56
12/8V3750GL	8V	9525	375.00	74.70	164.54
2/8V4000GL	8V	10160	400.00	13.28	29.25
3/8V4000GL	8V	10160	400.00	19.92	43.88
4/8V4000GL	8V	10160	400.00	26.56	58.50
5/8V4000GL	8V	10160	400.00	33.20	73.13
12/8V4000GL	8V	10160	400.00	79.68	175.51
2/8V4250GL	8V	10795	425.00	14.11	31.08
3/8V4250GL	8V	10795	425.00	21.17	46.62
4/8V4250GL	8V	10795	425.00	28.22	62.16
5/8V4250GL	8V	10795	425.00	35.28	77.70
12/8V4250GL	8V	10795	425.00	84.66	186.48
2/8V4500GL	8V	11430	450.00	14.94	32.91
3/8V4500GL	8V	11430	450.00	22.41	49.36
4/8V4500GL	8V	11430	450.00	29.88	65.81
5/8V4500GL	8V	11430	450.00	37.35	82.27
12/8V4500GL	8V	11430	450.00	89.64	197.44
2/8V4750GL	8V	12065	475.00	15.77	34.74
3/8V4750GL	8V	12065	475.00	23.66	52.10
4/8V4750GL	8V	12065	475.00	31.54	69.47
5/8V4750GL	8V	12065	475.00	39.43	86.84
12/8V4750GL	8V	12065	475.00	94.62	208.41

GOLD LABEL Banded Narrow - Size List



V-Belt Banded

GOLD LABEL.



Metric			
Section	W - Width (mm)	H - Height (mm)	Weight (Kg/rib*m)
3V	9	10	0.099
5V	15	15.5	0.272
8V	25	25.5	0.654

Imperial			
Section	W - Width (in)	H - Height (in)	Weight (lb/rib*in)
3V	23/64	25/64	0.006
5V	19/32	39/64	0.015
8V	1	1	0.037

DAYCO Part Nr	Section	Lo Outside length (mm)	Lo Outside length (in)	Weight (Kg)	Weight (lbs)
2/8V5000GL	8V	12700	500.00	16.60	36.56
3/8V5000GL	8V	12700	500.00	24.90	54.85
4/8V5000GL	8V	12700	500.00	33.20	73.13
5/8V5000GL	8V	12700	500.00	41.50	91.41
12/8V5000GL	8V	12700	500.00	99.60	219.38
2/8V5600GL	8V	14224	560.00	18.59	40.95
3/8V5600GL	8V	14224	560.00	27.89	61.43
4/8V5600GL	8V	14224	560.00	37.18	81.90
5/8V5600GL	8V	14224	560.00	46.48	102.38
12/8V5600GL	8V	14224	560.00	111.55	245.71
2/8V5900GL	8V	14986	590.00	19.59	43.15
3/8V5900GL	8V	14986	590.00	29.38	64.72
4/8V5900GL	8V	14986	590.00	39.18	86.29
5/8V5900GL	8V	14986	590.00	48.97	107.86
12/8V5900GL	8V	14986	590.00	117.53	258.87